

## CLASSIC FLOOR DECOR FLOOR TILE COATING

### PRODUCT DESCRIPTION

- Classic Floor Decor Floor Tile Coating is especially formulated for your exterior Floor Tiles
- It's having excellent strength and scrub resistance to with stand in harsh climatic condition.
- Excellent coverage
- Stain resistant

Recommended Uses - Specially formulated for application on Exterior Floor Tiles  
Packing - 1 Ltr, 4 Ltr, 10 Ltr and 20 Ltr

### HOW TO APPLY

#### Pre Painting Steps

- Surface should be clean, dry and free from any loose paint film
- Remove all loose and flaking material by scraping with a paint scraper, wire brush or by sanding.

#### Application

- Clean the tiles.
- Thin with clean water in the proportion of 2: 1 ratio.
- Apply by Brush /Spray, airless spray.

### ADDITIONAL INFORMATION

#### Technical Details

- Surface dry ; less than 30 minutes
- Hard Dry : 4 hrs
- Shelf life : 1 year from the date of manufacturing.
- Resistance to growth of algae &fungi : Resistant
- Coverage (in sq.ft) : 90 to 100 for 1 coat application  
60 to 70 for 2 coat application

(Coverage may vary from the quoted coverage on the basis of method of application and surface roughness)

## CLASSIC FLOOR DECOR FLOOR TILE COATING

### Precautions

- Mix well before use.
- Do not over thin.
- During application ensure adequate ventilation.

### Safety Features

- Store the container with lid tightly closed.
- Keep out of reach of children and away from food, drink.
- Inhalation /Injection is dangerous.
- Store away from direct sunlight, heat open fire and water.
- Do not pour the leftover paints in drains. Dispose off the paint left overs and containers as per local regulations.
- Use safety equipment like gloves, glasses or face mask.
- In case of contact with eyes seek immediate medical attention.
- Splashes on skin should be cleaned and washed off with soap and water.
- Recommended to use nose pad or masks while using.

### Disclaimer

The information in this document is given to the best of Classic Paints knowledge, based on laboratory testing and practical experience. Users should always consult Classic Paints for specific guidance on the general suitability of this product for their needs and specific application practices.