

CLASSIC ROYAL TOUCHE

PRODUCT DESCRIPTION

- Classic Royal Touché Luxury Interior Sheen is provides a luxurious finish and sheen appearance to your walls.
- Low VOC standards and free from heavy metals such as Lead, Mercury, Arsenic, chromium etc.
- Low Odour.
- Prevent Fungal growth and offers anti-bacterial shade to walls.

Colours Available - More than 1000 shades.

Recommended Uses - Specially formulated for application on Interior Walls.

Packing - 1 Ltr, 4 Ltr, 10 Ltr and 20 Ltr

HOW TO APPLY

Pre Painting Steps

- Surface should be clean, dry and free from any loose paint film
- Remove all loose and flaking material by scraping with a paint scraper, wire brush or by sanding.

Application

- Clean the surfaces.
- Thin with clean water in the proportion of 2:1 ratio (Paint: Water).
- Apply by Brush /Spray, airless spray.

ADDITIONAL INFORMATION

Technical Details

- Surface dry ; less than 30 minutes
- Hard Dry : 4 hrs
- Shelf life : 1 year from the date of manufacturing.
- Resistance to growth of algae &fungi : Resistant
- Coverage (in sq.ft) : 130 to 140 for 1 coat application
90 to 100 for 2 coat application

(Coverage may vary from the quoted coverage on the basis of method of application and surface roughness)

CLASSIC ROYAL TOUCHE

Precautions

- Mix well before use.
- Do not over thin.
- During application ensure adequate ventilation.

Safety Features

- Store the container with lid tightly closed.
- Keep out of reach of children and away from food, drink.
- Inhalation /Injection is dangerous.
- Store away from direct sunlight, heat open fire and water.
- Do not pour the leftover paints in drains. Dispose off the paint left overs and containers as per local regulations.
- Use safety equipment like gloves, glasses or face mask.
- In case of contact with eyes seek immediate medical attention.
- Splashes on skin should be cleaned and washed off with soap and water.
- Recommended to use nose pad or masks while using.

Disclaimer

The information in this document is given to the best of Classic Paints knowledge, based on laboratory testing and practical experience. Users should always consult Classic Paints for specific guidance on the general suitability of this product for their needs and specific application practices.